

805TSV 8" Touchscreen LCD Monitor with VGA & AV Inputs



Description

NOTE: This 8" Monitor is now special order only. For something readily available without MOQ, please take a look at the Sunlight Reable counterpart 802TSH.

Xenarc Technologies Corp. followed up the success of the 800 series line of displays with the introduction of the 805 series, an 8" LCD Touchscreen with VGA input utilizing the latest LED Backlight technology.

This affordable, yet versatile product incorporates the innovation of our VGA 8" model along with a 5-wire resistive Touch-Screen panel. Use the convenient touch-screen as your input device, control your mouse cursor or the mini on screen keyboard that comes with your operating system. The touch screen utilizes the USB port as the interface. You can connect several of our touchscreen displays to your device and the touchscreens would work simultaneously through the multi-monitor support. This unit is also available without Touch Screen as the 805YV.

Why do our products outlast others at extreme environments? Why do our products have wider temperature range and wider voltage input range? It is because our mission is to offer our customers the best. By utilizing high grade components, this monitor is perfect for industrial, in-car computing applications or any other applications where a small, durable display is required. Our displays are designed for applications such as but not limited to:

- **Transportation** - Marine, Air, Heavy Vehicles, Mining, Weigh Stations, Fleet Management, Telematics, In-Car Computing, Public Transit, Cargo
- **System Integration** - Machinery Controls, Factory Automation, Environmental Monitoring, Home Automation, Military, Smart Home
- **Point of Sale** - Hospitality, Digital Signage, Self-Service Kiosks, Outdoor Kiosks and Signage, Casino
- **Data Monitoring** - Cloud, IoT, Medical, Logistics, Inventory Management, Oil & Gas/Utilities, Law Enforcement, Broadcasting, Veterinary, First Person View
- **Broadcast & Production** - Broadcast Stations, Mobile Production Vehicles, Field Rugged Deployment for your mobile workforce, Studio Video Production

Features

NOTE: This 8" Monitor is now special order only. For something readily available without MOQ, please take a look at the Sunlight Reable counterpart 802TSH.

- 400NIT High Brightness Long Life LED Backlight
- Adjustable LED Backlight for nighttime use
- 5-Wire Resistive Touchscreen (USB)
- Anti-Glare Coating
- Multi-Monitor Touchscreen Support
- VGA Input (15 pin D-SUB) x 1 & Video Input x 2
- Audio Input x 3 / Built-In Speaker
- 800x600 Native Resolution, 4x3 Aspect Ratio
- Solid Capacitors for Improved Durability
- High Performance Image and Video Signal Processor
- **AISS** - Advanced Image-Scaling and Shaping
- Last Input and Power Setting Memory
- IR Remote Control
- Auto Power-On upon signal detection
- Mirror and Vertical Image Flip
- Function to Disable Front Button(s) and On Screen Text
- AV2 Auto Switching for Backup Camera

- Heavy Duty Monitor Stand
- VESA 75mm Mounting Holes
- 26-Pin Heavy-Duty Connector with Connector Locking
- Supports 9V DC ~ 36V DC
- "E" Mark Certified for Automotive use
- FCC, CE, E13 Certification
- ROHS, REACH, ECE R118-03 Compliant
- 36 Month/3 Year Warranty
- 30 Day No dead Pixel Guarantee


Function Diagram

How does it work?

- Connect the included cable to the Monitor
- Connect the connectors to your devices
- Install Touch Screen Driver



[TSV SERIES]



Package Contents

- Monitor Stand
- AC Adaptor or Cigarette Lighter Car Adaptor or 5M Power Lead
- 1.8M Connection Cable (5M version available separately)
- Optional Stylus

Specification

NOTE: This 8" Monitor is now special order only. For something readily available without MOQ, please take a look at the Sunlight Reable counterpart 802TSH.

- Screen Size: Diagonal 8" (4:3)
- Physical Resolution: 800 (H) x 600 (V) SVGA
- Supported Resolution: 640 x 480 ~ 1600 x 1200
- Dot Resolution: 2400 x 600 = 1,440,000 (dots)
- LCD Brightness: 400 cd/m²
- Contrast Ratio: 500:1
- Viewing Angle: 140° Horizontal, 120° Vertical
- Response Time (Tr/Tf): 10/15ms (Typ.)
- Touch Screen Interface: USB port
- Operating Voltage Range: DC 9V ~ 36V
- Power Supply: DC 12V
- Power Consumption: < 14W
- Operating Temperature: -4°F ~ 158°F (-20°C ~ 70°C)
- Storage Temperature: -22°F ~ 176°F (-30°C ~ 80°C)
- MTBF (Mean Time Between Failures): > 55,000 Hours or > 6.2 Years of continuous operation
- Dimension (mm): 200W x 163H x 36.5D
- Weight (lb): 1.81